


The VE Enclosed Home Lift



























BS5900:2012

Safety Quality

Stylish Functional Flexible









VE15/VE25 Models

Features & Options







In-Car Controls - 24v DC

Seat Option

In-Car Emergency Phone

Interior Lighting

Power Door Option

Wireless Landing Controls

Emergency Lowering

Underside Safety Edges

Roof Safety Sensor

Technical Specification

Standard Specifications	VE15/VE25	VE31/VE51	VE36/VE56	VE38/VE5
Small Enclosed Lift	✓	-	-	-
Standard Enclosed Lift	-	✓	-	-
Large Enclosed Lift	-	-	✓	-
Extra Large Enclosed Lift	-	-	-	✓
3m Maximum Travel	VE15	VE31	VE36	VE38
3.5m Maximum Travel	VE25	VE51	VE56	VE58
Internal Cabin Width	775mm	725mm	775mm	885mm
Internal Cabin Length - Manual Door*	575mm	1145mm	1195mm	1365mm
External Cabin Length With Door Open To Wall	1665mm	2190mm	2290mm	2570mm
External Width Including Floating Platform	920mm	870mm	920mm	1030mm
External Length Including Floating Platform	905mm	1475mm	1525mm	1695mm
External Cabin Length To Wall	840mm	1410mm	1460mm	1630mm
Internal Cabin Height	2000mm	2000mm	2000mm	2000mm
External Cabin Height 3m Models	2080mm	2080mm	2080mm	2080mm
External Cabin Height 3.5m Models	2220mm	2220mm	2220mm	2220mm
Minimum First Floor Ceiling Height 3m Models	2180mm	2180mm	2180mm	2180mm
Minimum First Floor Ceiling Height 3.5m Models	2315mm	2315mm	2315mm	2315mm
Mid-Floor Dimensions	From 165 - 385mm			
Safe Working Load	250kg			

^{*}Internal Cabin Length reduced by 30mm when the power door option is selected

British Design & Manufacture





E: enquiries@inclusivecaresolutions.co.uk



[✓] CE Marked